

I claim:

- Sub  
all  
5
1. An image controller for at least in part controlling an image generation machine, said image generation machine for controlling imagery shown by a display;
    - said image controller comprising,
      - a member graspable by a human user's hand;
      - a first button, said first button at least in part exposed exterior of said member to be depressible by a finger of a hand grasping said member, said first button structured to rotate upon depression by a finger,
      - a first proportional sensor, said first proportional sensor mounted within said member and activatable by rotation of said first button;
      - a second button, said second button at least in part exposed exterior of said member to be depressible by a finger of a hand grasping said member, said second button structured to rotate upon depression by a finger,
      - a second proportional sensor, said second proportional sensor mounted within said member and activatable by rotation of said second button,
      - the first and second buttons are variably depressible, and the first and second proportional sensors are structured to vary electrical output related to variable depression of the associated buttons, said output communicated to
      - the image generation machine causing imagery shown by the display to be variably controlled through variable depression of the first and second buttons;
      - a two-axes input structure at least in part supported by said member, said two-axes input structure associated with sensors for sensing two axes of inputs;
      - the first and second proportional sensors are at least in part connected to a sheet;
      - the sensors associated with said two-axes input structure are at least in part connected to said sheet;
      - active tactile feedback means for providing feedback to a hand grasping said member, said active tactile feedback means

09893290.062601

is positioned within said member.

2. An image controller according to claim 1 further comprising

5 a third proportional sensor is pressure-sensitive and includes a resilient dome cap, and

a fourth proportional sensor is pressure-sensitive and includes a resilient dome cap;

10 the resilient dome caps of the third and the fourth proportional sensors are each structured to provide a break-over tactile feedback.

15 3. An image controller according to claim 2 further comprising the resilient dome caps of the third and the fourth proportional sensors are each structured with a portion to impinge against an underlying electrically conductive element, said electrically conductive element at least engaging circuit traces when impinged upon.

20 4. An image controller according to claim 3 further comprising the portions of the resilient dome caps of the third and fourth proportional sensors, the portions which impinge against the underlying electrically conductive elements, are substantially convex shaped portions.

5. An image controller according to claim 4 further comprising

said circuit traces supported on said sheet.

25 6. An image controller according to claim 5 further comprising

said active tactile feedback means includes a motor.

7. An image controller according to claim 6 further comprising

30 an offset weight mounted on a shaft of said motor.

09893292-062501

8. An image controller according to claim 7 wherein said controller is a hand held three-dimensional graphics controller.

5 9. An image controller according to claim 1 wherein the sensors associated with said two-axes input structure are two bi-directional sensors.

10. An image controller according to claim 1 wherein the sensors associated with said two-axes input structure are four uni-directional sensors.

10 11. An image controller according to claim 10 wherein said two-axes input structure includes four resilient dome caps.

12. An image controller for at least in part controlling an image generation machine, said image generation machine for controlling imagery;

15 said image controller comprising,  
a member graspable by a human user's hand;  
a first pivotally mounted button, said first pivotally mounted button at least in part exposed exterior of said member to be depressible by a finger of a hand grasping said member,

20 a first proportional sensor, said first proportional sensor mounted within said member and activatable by depression of said first pivotally mounted button;

25 said first pivotally mounted button is variably depressible, and said first proportional sensor is structured to vary electrical output related to variable depression of the pivotally mounted button, said output communicated to

30 the image generation machine causing imagery to be variably controlled through variable depression of said first pivotally mounted button;

active tactile feedback means for providing feedback to a

09893292-062601

hand grasping said member, said active tactile feedback means is positioned within said member.

13. An image controller according to claim 12 further comprising

5 a second pivotally mounted button, said second pivotally mounted button at least in part exposed exterior of said member to be depressible by a finger of a hand grasping said member,

10 a second proportional sensor, said second proportional sensor mounted within said member and activatable by depression of said second pivotally mounted button;

15 said second pivotally mounted button is variably depressible, and said second proportional sensor is structured to vary electrical output related to variable depression of the second pivotally mounted button, said output communicated to

the image generation machine causing imagery to be variably controlled through variable depression of said second pivotally mounted button.

20 14. An image controller according to claim 13 further comprising

a two-axes input structure at least in part supported by said member, said two-axes input structure associated with sensors for sensing two axes of inputs.

25 15. An image controller according to claim 14 further comprising

the first and second proportional sensors are at least in part connected to a sheet.

30 16. An image controller according to claim 15 further comprising

the sensors associated with said two-axes input structure are at least in part connected to said sheet.

09893292-062501  
FO9290-2625550

a third proportional sensor activated by a single-finger depressible individual button, and

18. An image controller according to claim 17 further comprising

said fourth proportional sensor is pressure-sensitive and includes a resilient dome cap.

20. An image controller according to claim 19 further comprising the resilient dome caps of the third and the fourth proportional sensors are each structured with a portion to impinge against an underlying electrically conductive element, said electrically conductive element at least engaging circuit traces when impinged upon.

22. An image controller according to claim 21 further comprising

said circuit traces supported on said sheet.

said active tactile feedback means includes a motor.

an offset weight mounted on a shaft of said motor.

25. An image controller according to claim 24 wherein said controller is a hand held three-dimensional graphics controller.

```

a housing;
a first two-axes input structure supported by said housing;
a second two-axes input structure supported by said
housing;

```

active tactile feedback means for providing a feedback to a human user of said controller, said active tactile feedback means supported by said housing.

20 27. A hand operable image controller according to claim 26 wherein said active tactile feedback means includes a motor having a shaft with an offset weight mounted on said shaft.

25        said first two-axes input structure is associated with  
sensors for interpreting two-axes of input, and

a sheet connects the sensors of the first and second two-axes input structures.

30. A hand operable image controller according to claim 29 wherein said button is associated with a proportional sensor, and said button is variably depressible causing said proportional sensor to create a signal representing the variable depression of said button, said signal causing said imagery to vary according to the variable depression of said button.

32. A hand operable image controller according to claim 31 further comprising  
a resilient dome cap associated with said proportional sensor,  
said proportional sensor is a pressure-sensitive sensor.

34. A hand operable image controller according to claim 33 wherein said resilient dome cap contains a generally convexed surface area located within the dome.

36. A hand operable image controller according to claim 30 wherein said button is pivotally mounted.

17. A hand operable image controller according to claim 36 wherein the proportional sensor associated with the pivotally mounted button is a rotary sensor.

5 38. A hand operable image controller according to claim 37 wherein said rotary sensor is a potentiometer.

39. A hand operable image controller according to claim 30 wherein  
said first two-axes input structure is associated with  
sensors for interpreting two-axes of input, and  
10 said second two-axes input structure is associated with  
sensors for interpreting two-axes of input, and  
a sheet connects the sensors of the first and second two-  
axes input structures, and said sheet also connects  
said proportional sensor of said single-finger depressible  
15 independent button.

40. A hand operable image controller according to claim 39 wherein said sheet is a circuit board sheet.

41. A hand operable image controller according to claim 39 wherein said sheet is a flexible membrane sheet.

20 42. A hand operable image controller according to claim 33 wherein  
said first two-axes input structure is associated with  
sensors for interpreting two-axes of input, and  
said second two-axes input structure is associated with  
25 sensors for interpreting two-axes of input, and  
a sheet connects the sensors of the first and second two-  
axes input structures, and said sheet also connects  
said pressure-sensitive sensor of said button.

09893292.062601  
T09290.2626850



43. A hand operable image controller according to claim 42 wherein said sheet is a circuit board sheet.

44. A hand operable image controller according to claim 42 wherein said sheet is a flexible membrane sheet.

5 45. A hand operable image controller according to claim 37 wherein  
said first two-axes input structure is associated with  
sensors for interpreting two-axes of input, and  
said second two-axes input structure is associated with  
10 sensors for interpreting two-axes of input, and  
a sheet connects the sensors of the first and second two-  
axes input structures, and said sheet connects  
said rotary sensor of the pivotally mounted button.

15 46. A hand operable image controller according to claim 45 wherein said sheet is a circuit board sheet.

47. A hand operable image controller according to claim 45 wherein said sheet is a flexible membrane sheet.

48. A method of controlling imagery comprising the steps  
of:  
20 depressing, variably, a finger depressible button, said  
button  
pivoting, variably, causing variable  
activating of a proportional sensor, said proportional  
sensor  
25 outputting a signal useful to an image generation machine  
for  
causing imagery to vary according to the variable  
depressing of said button.

0993292-062601

49. A method of controlling imagery according to claim 48 further comprising the steps of:

depressing, variably, a second finger depressible button, the second button

5 pivoting, variably, causing variable

activating of a second proportional sensor, said second proportional sensor

10 outputting a second signal useful to the image generation machine for causing imagery to vary according to the variable depressing of said second button.

50. A method of controlling imagery according to claim 49 further comprising the step of:

providing an active tactile feedback.

15 51. A method of controlling imagery according to claim 50 further comprising the step of:

operating, variably, a two-axes input structure associated with proportional sensors for variably controlling said imagery.

20 52. A method of controlling imagery according to claim 51 further comprising the step of:

operating, variably, a second two-axes input structure associated with proportional sensors for variably controlling said imagery.

25 53. A method of controlling imagery according to claim 52 further comprising the step of:

depressing, variably, a third finger depressible button for variably controlling said imagery.

30 54. A method of controlling imagery according to claim 52 further comprising the step of:

operating a third two-axes input structure.

09893292.062601

55. A method of controlling imagery according to claim 54 further comprising the step of:

depressing, variably, a third finger depressible button for variably controlling said imagery.

5 56. A method of navigating a viewpoint within a three-dimensional graphics display, comprising the steps of:  
variably depressing a pivotal button, said pivotal button activating a proportional sensor, said proportional sensor outputting a signal at least in part useful for variably  
10 navigating the viewpoint.

57. A method of navigating a viewpoint according to claim 56 further including the step of  
supplying active tactile feedback.

15 58. A method of navigating a viewpoint according to claim 57 further including the steps of:  
variably depressing a second pivotal button, said second pivotal button  
activating a second proportional sensor, said second proportional sensor  
20 outputting a second signal at least in part useful for variably navigating the viewpoint.

25 59. A method of navigating a viewpoint according to claim 58 further including the step of:  
operating, variably, a two-axes input structure for variably navigating the viewpoint.

60. A method of navigating a viewpoint according to claim 59 further including the step of:  
operating, variably, a second two-axes input structure for variably navigating the viewpoint.

09893292-062601

61. A method of navigating a viewpoint according to claim  
60 further including the step of:

5     depressing with varying pressure, a single-finger  
depressible button associated with a pressure-sensitive sensor  
and a resilient dome cap having a substantially convexed  
portion for impinging electrically conductive material.

62. A method of navigating a viewpoint according to claim  
60 further including the step of:

10     operating, variably, a third two-axes input structure for  
variably navigating the viewpoint.

63. A method of navigating a viewpoint according to claim  
62 further including the step of:

15     depressing with varying pressure, a single-finger  
depressible button associated with a pressure-sensitive sensor  
and a resilient dome cap having a substantially convexed  
portion for impinging electrically conductive material.

64. A method of controlling an object shown by a  
three-dimensional graphics display, comprising the steps of:  
20     variably depressing a pivotal button, said pivotal button  
activating a proportional sensor, said proportional sensor  
outputting a signal at least in part useful for variably  
controlling the object.

65. A method of controlling an object according to claim  
64 further including the step of

25     receiving active tactile feedback.

66. A method of controlling an object according to claim  
65 further including the steps of:

30     variably depressing a second pivotal button, said second  
pivotal button  
activating a second proportional sensor, said second  
proportional sensor

09893292-062601

67. A method of controlling an object according to claim 66 further including the step of:

68. A method of controlling an object according to claim  
67 further including the step of:

69. A method of controlling an object according to claim  
68 further including the step of:

70. A method of controlling an object according to claim  
68 further including the step of:

71. A method of controlling an object according to claim  
70 further including the step of:

25        depressing with varying pressure, a single-finger  
depressible button associated with a pressure-sensitive sensor  
and a resilient dome cap having a substantially convexed  
portion for impinging electrically conductive material, said  
depressing with varying pressure for variably controlling the  
30        object.

72. A method of controlling imagery, comprising the steps of:  
pressing, variably, a first button for varying the imagery,  
receiving a first break-over tactile feedback.

5 73. A method of controlling imagery according to claim 72 wherein said receiving of said first break-over tactile feedback is preceded by the variable pressing of said first button.

10 74. A method of controlling imagery according to claim 72 further comprising the steps of:  
pressing, variably, a second button for varying the imagery,  
receiving a second break-over tactile feedback.

15 75. A method of controlling imagery according to claim 74 wherein said receiving of said second break-over tactile feedback is preceded by the variable pressing of said second button.

20 76. A method of controlling imagery according to claim 74 further comprising the step of:  
inputting variably, two-axes inputs using a first two-axes structure, said inputting variably for varying the imagery.

25 77. A method of controlling imagery according to claim 76 further comprising the step of:  
inputting variably, two-axes inputs using a second two-axes structure, for varying the imagery.

78. A method of controlling imagery according to claim 77 further comprising the step of:  
depressing with varying pressure a single-finger depressible button for varying the imagery.

10989329.062501

79. A method of controlling imagery according to claim 77 further comprising the step of:

inputting two-axes inputs using a third two-axes structure, for controlling the imagery.

5 80. A method of controlling imagery according to claim 79 further comprising the step of:

depressing with varying pressure a single-finger depressible button for varying the imagery.

10 81. A method of controlling imagery by controlling variable output of at least one variable output sensor actuated by a single finger depressible button, comprising the steps:

pressing, variably, said button, thus  
actuating said sensor, said sensor  
15 outputting a signal, said signal representing intensity of the pressing,  
varying the imagery according to said signal,  
providing, at least through said button, a break-over tactile feedback.

20 82. A method of controlling imagery according to claim 81 wherein a second variable output sensor is actuated by a second single finger depressible button, further comprising the steps:

pressing, variably, said second button, thus  
25 actuating said second sensor, said second sensor outputting a second signal, said second signal representing intensity of the pressing of said second button,  
varying the imagery according to said second signal,  
providing at least through said second button a second  
30 break-over tactile feedback.

83. A method of controlling imagery according to claim 82 further comprising the step of:

providing an active tactile feedback.

00003292.062601

~~operating a first two-axes input structure for varying the imagery.~~

86. A method of controlling imagery according to claim 85 further comprising the step of:  
depressing with varying pressure a third finger depressible button causing varying change of said imagery.

88. A method of controlling imagery according to claim 87 further comprising the step of:  
depressing with varying pressure a fourth finger depressible button causing varying change of said imagery.

89. A method of manufacturing a hand operable image controller for controlling imagery, comprising the steps of:  
installing a pivotally moveable button as a part of said image controller, and  
25 installing a proportional sensor positioned to be activated by pivoting motion of said pivotally moveable button, and  
installing circuitry for reading said proportional sensor and causing the imagery to change variably according to said pivoting motion of said pivotal button.



90. A method of manufacturing a hand operable image controller according to claim 89 further comprising the steps of:

5 installing a first two-axes input structure as part of said controller,  
installing active tactile feedback means.

10 91. A method of manufacturing a hand operable image controller according to claim 90, further comprising the steps of:

installing a second pivotally moveable button as part of said image controller, and  
installing a second proportional sensor positioned to be activated by pivoting motion of said second pivotally moveable button, and  
15 installing a second two-axes input structure as part of said controller.

20 92. A method of manufacturing a hand operable image controller according to claim 91, further comprising the step of:

installing a third two-axes input structure as part of said controller.

25 93. A method of manufacturing a hand operable image controller according to claim 92, further comprising the step of:

installing a pressure-sensitive button for variably controlling imagery in relation to pressure applied to said pressure-sensitive button.

30 94. A method of manufacturing a hand operable image controller according to claim 93, further comprising the step of:

installing a sheet, said sheet supporting electrical circuit traces and said sheet connecting the proportional

109893292.062601

95. A method of manufacturing a hand operable image controller for at least in part controlling an image generation machine, said image generation machine for controlling imagery shown by a display; the method comprising the steps of:

installing a first proportional sensor, said first  
15 proportional sensor mounted within said housing and  
activatable by rotation of said first button;

installing a second proportional sensor, said second proportional sensor mounted within said housing and activatable by rotation of said second button;

installing a two-axes input structure at least in part supported by said housing, said two-axes input structure associated with sensors for sensing two axes of inputs;

installing a sheet at least in part supporting said  
35 circuitry, said sheet connecting the first and second

proportional sensors, said sheet also connecting the sensors associated with said two-axes input structure;

5 installing a motor and weight for providing feedback to a hand grasping said housing, said motor is positioned within said housing.

96. A method of manufacturing a hand operable image controller according to claim 95 further including the steps:

installing a third proportional sensor to be activated by human input, and

10 installing a fourth proportional sensor to be activated by human input;

said third proportional sensor is pressure-sensitive and includes a resilient dome cap, and

15 said fourth proportional sensor is pressure-sensitive and includes a resilient dome cap;

the resilient dome caps of the third and the fourth proportional sensors are each structured to provide a break-over tactile feedback.

10989322-062501